(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification⁷: H04Q 7/18, 7/20, 7/22, H04M 1/57, 1/65, 3/50

(21) International Application Number: PCT/US01/11795

(22) International Filing Date: 11 April 2001 (11.04.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/196,097   11 April 2000 (11.04.2000)   US
60/196,101   11 April 2000 (11.04.2000)   US

(71) Applicant: TELECOMMUNICATION SYSTEMS, INC. [US/US]; Suite 400, 275 West Street, Annapolis, MD 21401 (US).

(72) Inventors: SMITH, Richard, A.; 12 North Southwoods Avenue, Annapolis, MD 21401 (US). DEWEY, Michael; 271 Yale Court, Arnold, MD 21012 (US).

(74) Agent: BOLLMAN, William, H.; Manelli Denison & Selter PLLC, Suite 700, 2000 M Street, NW, Washington, DC 20036-3307 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(54) Title: INTELLIGENT DELIVERY AGENT FOR SHORT MESSAGE DISTRIBUTION CENTER

(57) Abstract: A message distribution center (MDC) (100) and Intelligent Delivery Agent (318) are implemented in a wireless Internet gateway interposed between content providers (120) and a wireless carrier (130) to subjectively examine and direct messages via SMTP based on desired rules using standard SMTP Gateway and other well-known protocols. The MDC (100) includes an individual queue for each subscriber, and the provider is informed through conventional SMTP protocol messages that the short message has been accepted. If the carrier has specifically disallowed service for a particular MIN, then the content provider (120) is informed through an SMTP interchange that the recipient is invalid. An MDC (100) provides a single mechanism for interacting with subscribers of multiple carriers (130), regardless of each carrier's underlying infrastructure. In the disclosed embodiment, a

INTELLIGENT DELIVERY AGENT FOR SHORT MESSAGE DISTRIBUTION CENTER

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates generally to wireless carriers, Internet service providers (ISPs), and information content delivery services/providers. More particularly, it relates to Wireless Telecommunication, ANSI-41D Wireless Intelligent Network (WIN) applications, and SMTP protocol to manage information content for a wireless carrier.

2. Background of Related Art

There are many "wireless" information content providers in the industry who have some information or service that is considered of value to the mobile phone user. Wireless Carriers are typically in favor of these content providers as they add value to Short Messaging Systems (SMS) and can drive up SMS and voice usage.

Unfortunately, content providers may not fully understand a particular wireless network and/or may not be fully sensitized to particular needs of carriers. This is because the carrier is often seen simply as a 'pipe' through which wireless messages are sent using SMTP protocol. Content providers maintain their own subscriber lists, and typically communicate with carriers merely as e-mail hosts.

All traffic is typically sent through an SMTP gateway, and thus information content, ads, etc., cannot be differentiated from higher priority 'personal' content. Problems arising from this include:

- Bulk information content can slow down and even jeopardize the carrier's SMTP Gateway performance;

- Personal messages cannot be given a higher priority than bulk messages;

- Bulk info content receives the same messaging parameters as personal messages, e.g., delivery receipts enabled, expiration date of 3-5 days, etc.;

- The carrier cannot differentiate between bulk messages among various providers and personal mail for billing purposes;

- Bulk senders deliver their content regardless of whether the device is on, and thus the carrier must handle message storage and retry attempts; and

- Bulk senders will typically continue to deliver content to churned wireless subscribers, wasting network resources and interfering with reuse of mobile numbers.

There is a need for a technique using SMTP and/or other conventional protocols to enable an easy way for content providers to distribute and/or differentiate their information without requiring them to change technologies.

BRIEF DESCRIPTION OF THE DRAWINGS

Features and advantages of the present invention will become apparent to those skilled in the art from the following description with reference to the drawings, in which:

Fig. 1 shows a high level sequence diagram including a Message Distribution Center (MDC) enabling a Content Provider to direct messages via SMTP to the Message Distribution Center (MDC), in accordance with the principles of the present invention.

Fig. 2 illustrates exemplary software components and their relationships in an embodiment of a message distribution center (MDC), in accordance with one embodiment of the present invention.

Fig. 3 is an exemplary class diagram which shows further details of an embodiment of a Message Distribution Center, in accordance with the principles of the present invention.

SUMMARY OF THE INVENTION

In accordance with the principles of the present invention, a message distribution center is interposed between a source of a short message and a wireless network including an intended recipient of the short message. The message distribution center comprises an SMTP protocol communication channel to receive the short message from the source of the

2

short message.   A plurality of subscriber queues are included, each corresponding to a different subscriber in the wireless network.   The short message is placed in at least one of the plurality of subscriber queues before delivery to the wireless network. A communication channel communicates the
5   short message to the wireless network.

In accordance with another aspect of the present invention, a method of throttling short messages to subscribers in a wireless network comprises forwarding a short message to a wireless network only when a receiving wireless device in said wireless network is known outside said
10   wireless network to be online.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

The present invention enables a Content Provider to direct messages via SMTP to an intermediatary Message Distribution Center (MDC)
15   using standard SMTP Gateway and other well-known protocols.

In accordance with the principles of the present invention, short messages are inserted in the MDC into individual queues for each subscriber, and the provider is informed through conventional SMTP protocol messages that the short message has been accepted.

20   If the carrier has specifically disallowed service for a MIN (e.g., in the case of churning), then the content provider is informed through an SMTP interchange that the recipient is invalid. This encourages providers to discontinue service to terminated MINs, thereby reducing traffic to the MDC.

A Message Distribution Center (MDC) provides value to both
25   wireless developers and wireless carriers. For instance, for the Wireless Developer, an MDC provides a single mechanism for interacting with subscribers of multiple carriers, regardless of each carrier's underlying infrastructure. For the carrier, an MDC can protect their SS7 network by intelligently throttling messages and configuring message delivery parameters
30   to be more network friendly.

An MDC acts as a broker between carriers and developers. Different levels of relationships can be established with both carriers and developers, resulting in different levels of services that are available. The MDC interacts with a carrier's Short Message Service Center(s) (SMSCs)

and/or SS7 network, allowing developers to guarantee message delivery, to interact with users via Mobile Terminated (MT) and Mobile Originated (MO) SMS, and possibly even to receive handset presence information.

Although the disclosed embodiments relate primarily to wireless services from the perspective of a Short Message Service (SMS), the disclosed MDC and related management middleware may support many types of wireless devices using the same API. For instance, suitable supported devices may include, e.g., 2-way Email pagers, the Palm VII™, and wireless application protocol (WAP) devices.

The disclosed MDC utilizes a Wireless Internet Gateway (WIG), which is a middleware messaging platform designed to facilitate communication between Internet devices and various wireless networks. A suitable WIG is disclosed in U.S. Appl. No. 09/630,762 to SMITH, entitled "Wireless Internet Gateway", filed August 2, 2000, the entirety of which is expressly incorporated herein by reference.

Fig. 1 shows a high level sequence diagram including a Message Distribution Center (MDC) enabling a Content Provider to direct messages via SMTP to the Message Distribution Center (MDC), in accordance with the principles of the present invention.

In particular, as shown in Fig. 1, an MDC gateway (MDC) **100** and Intelligent Delivery Agent (IDA) **318** are placed intermediary between a content provider **120** and a wireless carrier **130**, to allow management of message delivery for each of a plurality of subscribers.

There are two main programs. The first application program is the MDC Gateway **100**, which is essentially a Wireless Internet Gateway to check for and process information provider messages as shown and described herein. The second application program is the Intelligent Delivery Agent (IDA) **318**.

As shown in Fig. 1, the content provider **120** communicates with the MDC **100** using SMTP protocol messages, and the MDC communicates with the wireless carrier **130** preferably using RMI/SMPP techniques. A plurality of configuration files **500** configured by an appropriate system administrator control parameters in the MDC **100** and IDA **318**.

Importantly, the MDC **100** includes a plurality of subscriber queues **150**, preferably one for each subscriber having MDC support. The subscriber queues **150** may be integrated within the gateway of the MDC **100**, or may be external to the gateway of the MDC **100** but nevertheless in direct communication with the gateway of the MDC **100**.

The subscriber queue **150** preferably follows a First In First Out (FIFO) model, where the oldest messages are delivered first.

In accordance with the principles of the present invention, a particular wireless carrier **130** assigns a value for the maximum number of outstanding messages for a particular subscriber. This maximum number of outstanding messages can be used to establish a queue threshold. Thus, if one or more new messages cause the queue threshold to be exceeded, then the oldest messages may be deleted first from the particular subscriber queue **150** to make room for the new message(s). Of course, the subscriber queue **150** may be expanded in size as desired.   To provide protection from constantly growing subscriber queues **150**, other rules may be established by the wireless carrier **130** to allow automatic deletion of particular messages from the subscriber queue **150**.

For instance, an expiration period may be established whereby all messages more than x days old are removed. The expiration period may be established, e.g., on an individual subscriber basis (e.g., different subscription plans allowing larger queues and/or longer storage times), or on a global basis (e.g., all subscribers in a particular wireless network have a similar expiration time).

The use of automatic deletion of short messages from subscriber queues **150** is important, e.g., in the case of churned MINs, so that a new subscriber does not receive lingering messages from a previous subscriber with the same MIN.

Short messages to subscriber queues **150** may be delivered independently from one another and/or message delivery times spaced apart, thereby distributing message load over time and minimizing the negative effects of batch messaging on the wireless network.

The MDC **100** can also or alternatively be configured to avoid sending batch messages during the carrier's busy hour(s), thereby minimizing load pressures on the wireless network.

The use of an MDC **150** can aid the wireless carrier's network significantly, e.g., by forwarding short messages only when the relative handsets are turned on. Under this scenario, subscriber queues are not processed when the handset is powered off. This can reduce network storage requirements, delivery retry attempts, and overall SS7 usage. The MDC **100** can do this either by interacting with appropriate applications, e.g., with a mobile chat location register (MCLR), or generally by intelligent use of SMS delivery receipt data from the SMSC and Web Gateway. A suitable mobile chat location register (MCLR) is shown and described in U.S. Appl. No. 09/814,363, entitled "Wireless Chat Automatic Status Tracking", filed March 23, 2001 by Ung et al., the entirety of which is expressly incorporated herein by reference.

The MDC **100** can further be configured to send content from various providers to certain SMPP ports on a short message service center (SMSC). The receipt of such content allows distinct billing records to be generated for each type of service, e.g., ads, general content, premium content, etc.

Fig. 2 illustrates exemplary software components and their relationships in an embodiment of a message distribution center (MDC), in accordance with one embodiment of the present invention.

In the disclosed embodiments, a Wireless Internet Gateway (WIG) was modified to include another 'dev/null' destination, which acknowledges short messages from a queueMonitor, but does not actually process them. The short messages remain in the *Messages* table of the database, where they are retrieved by a software component referred to herein as an "Intelligent Delivery Agent" (IDA).

The IDA retrieves messages from the *Messages* table in the database for subscribers, e.g., when they power on their handsets, subject to any desired rules. The IDA can become aware of subscriber power-ups through any appropriate trigger, e.g., via an SMPP Delivery Receipt mechanism, through Mobile Chat Location Register (MCLR) software, etc.

Preferably, the IDA throttles short message traffic to any or all subscribers, e.g., optionally waiting until the busy hour is over before beginning the transmission.

The MDC Gateway **100** may be, e.g., a standard WIG to which the provider sends messages through SMTP, RMI, HTTP, or suitable middleware software. As shown in Fig. 2, the MDC **100** includes a new *DummyDestination*, which simply acknowledges receipt from a particular subscriber queue **150**, but does not attempt delivery. Delivery may be accomplished through an Intelligent Delivery Agent process, which polls a messages table that is populated when the MDC Gateway **100** receives relevant short messages.

To most efficiently use the MDC gateway **100**, the SMTP session preferably assigns the msgType property based on the sender's Email address and using *InfoProviders* information from the database. This allows the MDC Gateway **100** to determine that SMTP messages from an Information Provider (e.g., <u>INFO@NEWS.COM</u>) should use the Dummy Destination and be queried by the IDA. If the short message is submitted via an RMI mechanism, then the sender will explicitly define the msgType.

When the MDC **100** inserts a short message record, an Oracle™ trigger may be used to create a subscriber record in the *Subscribers* table in the database if such a record does not already exist for the recipient.

The *Subscribers* table may contain, preferably at a minimum, a MIN, status (e.g., 'Online', 'Offline', 'Unknown'), and the time of the last status update. When first created, the status may default to 'Unknown'.

The IDA may be a separate program that delivers messages from the database to appropriate recipients via a RemoteSMPP RMI Interface of the carrier's gateway. The IDA preferably determines subscriber availability via, e.g., an MCLR or via Delivery Receipts. The former approach is likely more efficient, but the latter approach is more likely to work with most carrier environments.

The Delivery Receipt method is considered to be more complicated. The Delivery Receipt method attempts to find the status of a subscriber's handset by examining delivery receipts from messages sent to the subscriber.

As shown in Fig. 2, a *SubscriberPoller* agent **202** starts the process by gathering a list of subscribers from a *Subscribers* table **214** at some time interval (z). If a particular subscriber is online, then the *DeliveryAgent* object **210** is notified.

The *DeliveryAgent* **210** then gathers some pre-configured number of messages in time order for the subscriber from the *Messages* table **228** in the database, and sends them to the *Carrier gateway* **238** for delivery to the subscriber. There is no delivery receipt associated with these messages, so if the subscriber's handset is turned off the short messages are not delivered and not resent. This is why it is preferred that only a pre-configured number of short messages be sent before the subscriber's status is checked again by *SubscriberPoller* **202**.

If a subscriber's status is unknown, then a *DRDeliverAgent* **234** is notified to send one message via the *Carrier gateway* **238** to the subscriber with a delivery receipt requested. When it sends the message, it sets the subscriber status as offline so that the *SubscriberPoller* **202** will ignore that subscriber.

The delivery receipt will arrive at *DR Listener* **208**. If the delivery receipt indicates failure, then the subscriber status is set as 'unknown', otherwise the subscriber status is set as 'online'. The *SubscriberPoller* **202** wakes up shortly thereafter to take advantage of the user going online.

Because there is no direct feedback from the handset, there is no conventional information received when a handset is turned off or on. *DBSubStatusResetter* **204** makes assumptions about how long a handset typically stays on or goes off. If a handset has been marked as online for a period of time (x), then *DRSubStatusResetter* **204** sets the corresponding subscriber status to 'unknown', which will restart the delivery receipt cycle again. If a subscriber has been marked as 'offline' for a different period of time (y), then the subscriber is marked as unknown, again restarting the delivery receipt cycle.

To summarize, there are three time periods involved in the Delivery Receipt method. Time x is the average time that a handset is online. Time y is the average time that a handset is offline. Time z is how often the Subscribers table **214** is polled for a list of subscribers.

The three periods mentioned (x, y, and z) must have a certain relationship to one another. Time z must be smaller than time x and time y. Time x and time y's relationship to one another doesn't matter. Time z must be smaller than time x so that when a subscriber goes online, messages are

5   sent to it before time x expires and online subscribers are set to 'unknown'. Time z should be smaller than time y, otherwise the subscriber will be sent another message before DR Listener 208 has had a chance to receive the delivery receipt. This implies that time z will also be longer than the expected time for a delivery receipt.

10   A *SubscriberCleanUp* agent may be implemented to clean out subscribers that haven't had messages sent to them for a pre-defined period of time. This will ensure that the subscriber database doesn't grow without bound. Subscribers may have taken their name from the information provider's subscriber list.

15   Another technique mentioned above is to use an MCLR facility. In this situation, the MCLR will know explicitly when a handset is turned off or on. The *MCLR Listener* 218 then updates the *Subscribers* table 214 accordingly. The *SubscriberPoller* 202 always sees only online subscribers. It then uses the *DeliveryAgent* 210 to send the messages without a delivery

20   receipt requested.

When the *MCLR Listener* 218 is active, then the *DRDeliverAgent* 234, *DR Listener* 208, and *DBSubStatusResetter* 204 are all inactive. When the three delivery receipt entities are active, then the *MCLR Listener* 218 is inactive.

25   The *IDA Main* 232 activates appropriate facilities based on a configuration file.

In an MCLR implementation, the *DRDeliveryAgent* 234, *DR Listener* 208, and *DRSubStatusResetter* 204 may not be used.

Fig. 3 is an exemplary class diagram which shows further details

30   of an embodiment of a Message Distribution Center, in accordance with the principles of the present invention. In particular, Fig. 3 shows exemplary classes that may be activated and used to determine subscriber status and to actually deliver messages.

As shown in Fig. 3, an *IDA* main class **318** is responsible for deciding which subscriber status determination strategy to use. The IDA class **318** may receive this information from a configuration file. The IDA class **318** instantiates and activates an *MCLRListener* class **314** if that facility is to be used to retrieve a handset's online/offline status. If the strategy is to use delivery receipts, then the *IDA* class **318** instead instantiates and activates the *DRListener* **322** and *DRSubStatusResetter* **316** classes.

A *SubscriberPoller* **306** class gets a list of subscribers whose status is 'unknown' or 'online' from the database. If a subscriber's status is 'unknown', the *SubscriberPoller* **306** invokes a method in a *DeliveryAgent* class **302** to send a message requesting a delivery receipt. If the subscriber's status is 'online', then the *DeliveryAgent* **302** sends messages without a delivery receipt to the subscriber.

The *DeliveryAgent* **302** is responsible for averaging out the load on the carrier's system. It may do this by spreading out the messages over time, allowing normal traffic to be sent more quickly. The *DeliveryAgent* **302** may also hold off sending batch messages during the carrier's busy time. This information may be maintained in a configuration file and retrieved through a *DeliverySetupInfo* class.

The *DeliveryAgent* **302** can also be configured to send messages over certain SMPP ports to the carrier gateway **238** for tracking the amount of traffic that an information provider is sending. The DeliveryAgent **302** may accomplish this by tagging the message with a message type indicating that it is an MDC message. The configuration file may be set up so that messages of an MDC type will be sent to certain SMPP ports by the carrier gateway **238**.

Both the *Subscribers* **300** and *Messages* **304** classes may be wrappers around their respective database tables, to isolate JDBC calls to these classes only and/or to place the data in a useful format.

The IDA **318** may send messages and/or decide blackout periods on a global basis, i.e., regardless of the destination of any particular message. One enhancement to this is to apply these on a per-carrier basis since carriers can be in different time zones or have more or less capable hardware.

One advantage provided by the present invention is that SMTP is a well-known protocol and an easy way for content providers to distribute their information.

A Message Distribution Center (MDC) in accordance with the principles of the present invention provides an ideal solution. It addresses the problems faced by the carrier without requiring the information providers to change technologies.

The principles of the present invention have applicability for usage with wireless intelligent network (WIN) and SMTP applications, e.g., those already otherwise containing a Internet gateway application for routing information through an SMTP gateway. Moreover, the MDC allows content providers to continue with their current mode of operation without placing the carrier's network at risk. The MDC can receive messages using a variety of protocols, including SMTP. It automatically routes messages to the appropriate carrier based on MIN range. Instead of delivering SMTP content directly to the carrier, it is delivered to the MDC. The MDC then ensures that the content is delivered in a 'carrier-friendly' manner.

MDC can provide the Info Provider with delivery statistics, e.g., what percentage of messages are being delivered.

The MDC helps prevent the carrier from being overwhelmed by bulk messaging content and provides the following benefits:

- bulk message traffic is distributed across time
- messages are delivered over more efficient protocols than SMTP through the carrier's Wireless Internet Gateway
- messages are only delivered when handsets are on, thereby eliminating network storage and retries
- messages are delivered with appropriate urgency, delivery receipt, expiration times, and billing identifiers
- individual bulk message queues allow the carrier to limit the number of messages that can be queued per subscriber
- bulk messaging can be disabled for individual accounts when subscribers churn
- bulk message delivery statistics are available to the carrier via a web interface.

Acknowledgement of Delivery Receipts

It is preferred that remote gateways be sent to via a remote queue. This is because of the uncertainty about the link IDs which would be used by the remote gateway per MIN. Rather, all that is known is that a gateway takes a certain range of MINs. However, the gateway itself may partition out the MINs to be sent via different protocols such as SMPP, TNPP or others. That information is preferably not kept at the IDA **318**, preventing use of the remote SMPP classes. However, the remote queue has no provision for sending information back. It is preferred that this ability be provided so as to receive back delivery receipts.

In accordance with the principles of the present invention, a ReceiptNotifier class may be added to the code. When such a ReceiptNotifier class detects that a delivery receipt is to go back to the IDA **318** (i.e., a hostname or IP is in receiptEmail, receiptMIN or a new receipt field in the Message class **304**), it establishes a connection with the IDA **318** and sends back the receipt information.

Two exemplary methods to receive back at the IDA **318** the delivery receipt, both involving gateway software running at a remote site to recognize first that a delivery receipt is necessary. One was discussed above, while the other establishes a connection back to the IDA **318** and a protocol to use. In accordance with the principles of the present invention, RMI techniques may be used to accomplish this.

When the remote gateway sees an IDA delivery receipt request, it may perform a Naming.lookup() based on the URL in the delivery receipt field in the Message. It then sends the message name field from the Message and the delivery status. Once sent, it can abandon the object it got back from the Naming.lookup() call.

This implies that the remote gateway will be an RMI client to the IDA delivery receipt server. Typically the remote gateway has been acting as an RMI server. However, this scheme of being a client falls in line with how the SMTP delivery receipt is sent, that is, the remote gateway acts as a mail client in this case.

12

An IReceiptProxy interface **322** may be added to allow communication between the MDC gateway **100** and the IDA **318**. The *DRListener* agent **322** in the IDA **318** preferably acts as an RMI server to receive the acknowledgements from the MDC gateway class *ReceiptNotifier*. The *receiptEmail* field in the Message preferably contains the hostname to respond back to. *ReceiptNotifier* distinguishes between email addresses and host names in this field and sends the delivery receipt accordingly.

The IDA **318** is configured via appropriate configuration files, e.g., an ida.cfg file, an IdaRemoteHostInfo.properties file, and database tables (described more fully herein below). It is preferred that the IDA **318** use the same database as the MDC gateway **100**. The MDC gateway **100** and the IDA **318** preferably utilize tables and configuration/property files, which should be set up correctly. In operation, the setup of MDC and IDA configuration/property files is typically the responsibility of an MDC administrator. Exemplary values for configurable files are provided herein below.

The MDC **100** and IDA **318** work together to handle the large amount of traffic generated by information providers. The MDC **100** automatically routes messages to the IDA **318** based on if the message is from an information provider. Instead of delivering SMTP content directly to the carrier, the MDC **100** delivers it to the IDA **318**. The IDA **318** then ensures that the content is delivered in a 'carrier-friendly' manner.

The MDC Gateway **100** is started using a standard smsgw.sh script. The IDA **318** may be started separately with an ida.sh script. The only necessary dependency between the two programs is the database tables they share. This means that either can be started without the other running. However, nothing useful happens until both are running.

Table 1 describes relevant modules in the MDC Gateway **100**.

Module Name	Package
Base36.java	tcs.ain.smsgw
Config.java	tcs.ain.smsgw
DummyDestination.java	tcs.ain.smsgw
IReceiptProxy.java	tcs.ain.smsgw
Message.java	tcs.ain.smsgw
MessageStoreDB.java	tcs.ain.smsgw
ReceiptNotifier.java	tcs.ain.smsgw
SMPPReceiptMessage.java	tcs.ain.smpp
SMPPResource.java	tcs.ain.smpp
SMTPMessageData.java	tcs.ain.smsgw
SMTPSession.java	tcs.ain.smsgw

Table 1

5

Table 2 identifies relevant exemplary modules in an IDAm **318**, packed in the exemplary embodiment in a "tcs.ain.ida" package and located in a directory in the MDC gateway **100**, e.g., called "smswebgw".

Module Name
DRListener.java
DRSubStatusResetter.java
DeliveryAgent.java
HostInfo.java
IDA.java
IDAConfig.java
IdaDebug.java
InfoProviders.java
MCLRListener.java
Messages.java
RemoteGwInfo.java
SubscriberInfo.java
SubscriberPoller.java
Subscribers.java

10

Table 2

The MDC Gateway **100** uses a number of database tables. The following are exemplary configurable tables **500** specifically used by the MDC Gateway **100** and the IDA **318**.

5 **INFOPROVIDER Configuration Table**

An INFOPROVIDER table provides a list of information providers. If an information provider is on this list, the MDC Gateway **100** will route a relevant message to the IDA **318**. The INFOPROVIDER table is used only by the MDC Gateway **100**.

10 The INFOPROVIDER table is preferably configured by an appropriate system administrator.

Column	Data Type	Null?	Notes
MSGSENDER	CHAR(150)	N	Should match what the information provider puts in the sender field in mail
LASTUPDATE	NUMBER	Y	Currently unused. Should represent time when row was inserted
INFOPROVIDERID	NUMBER(9)	Y	
PROVIDERNAME	VARCHAR2(50)	Y	
SERVERID	VARCHAR(50)	Y	
SERVERPASSWORD	VARCHAR2(50)	Y	

Table 3

15

LINKID_NPANXX Configuration Table

A LINKID_NPANXX configurable table, used by both the MDC gateway **100** and the IDA **318** associates a MIN with a carrier's remote gateway. Link IDs are defined for each carrier in a GWDest.properties file from smswebgw/smsgw. The IdaRemoteHostInfo.properties file mentioned in

20 the next section should align with the link IDs.

Column	Data Type	Null?	Notes
LINKID	NUMBER(2)	Y	This number is an ID assigned to each carrier with a remote gateway to which the IDA can send messages.
NPA_NXX	VARCHAR2(6)	N	Represents the first 6 digits of a MIN and is used to assign a MIN to a remote gateway.

Table 4

5 ## MESSAGES Configuration Table

A MESSAGES table contains information about a message being sent. The MESSAGES table may be used by both the MDC gateway **100** and the IDA **318**.

Column	Data Type	Null?
MSGTYPE	NUMBER(2)	Y
MSGSOURCE	NUMBER(2)	Y
MSGSTATUS	NUMBER(2)	Y
MSGSUBSTATUSDESC	VARCHAR2(255)	Y
MSGMIN	VARCHAR2(30)	Y
MSGCALLBACK	VARCHAR2(30)	Y
MSGSENDER	VARCHAR2(150)	Y
MSGSUBJECT	VARCHAR2(255)	Y
MSGTEXT	VARCHAR2(2000)	Y
MSGSRCADDR	VARCHAR2(150)	Y
SMSCMSGID	VARCHAR2(10)	Y
RECEIPTEMAIL	VARCHAR2(70)	Y
RECEIPTMIN	VARCHAR2(30)	Y
RECEIPTCALLBACK	VARCHAR2(30)	Y
MSGNAME (the unique identifier (key))	VARCHAR2(20	N
SRCGWID	VARCHAR2(5)	Y
MSGARRIVE	NUMBER	Y
MSGSENT	NUMBER	Y
MSGFINAL	NUMBER	Y
MSGSUBMIT	NUMBER	Y
MSGEXPIRE	NUMBER	Y

10

Table 5

SUBSCRIBERS Configuration Table

A SUBSCRIBERS table is used internally by the IDA **318**. It keeps track of subscribers that have been sent messages by an information provider. The SUBSCRIBERS table is used by both the MDC Gateway **100** and the IDA **318**.

Column	Data Type	Null?	Notes
SUBSCRIBERMIN	VARCHAR2(30)	N	
STATUS	NUMBER(2)	N	Internal value (0-offline, 1-online, 2-unknown)
LASTSTATUSUPDATE TIME	NUMBER	Y	Last time the status was changed
LASTMSGTIME	NUMBER	Y	Last time the subscriber received a message

Table 6

There is only one trigger in the exemplary embodiments defined for the IDA **318**, called subsc_update. Whenever a message is added to the MESSAGES table, the subscriber is added or updated in the SUBSCRIBERS table if the message is from an information provider. This may be indicated, e.g., by bit 6 being set in an msgsource field.

IDA Configuration File

An ida.cfg file contains parameters that control the behavior of the IDA program **318**. It is preferred that the ida.cfg file reside in the same directory as the executing IDA program **318**. Table 7 shows exemplary parameters and values of an ida.cfg file, in accordance with the principles of the present invention.

Parameter	Purpose	Field Value	Field Explanation
General Parameters			
SubscriberStrategy	Strategy used to find subscriber status	DELIVERY_RECEIPT (default)	Have the remote gateway request a delivery receipt
		MCLR	Use mobile chat location register (not implemented yet)
debugmode	Used to set the IDA to print run-	true	Turn on run-time messages

Parameter	Purpose	Field Value	Field Explanation
	time debug messages	false (default)	Turn off run-time messages
RemoteQueueName	Name of remote queue to send messages to	RemoteQueue (default)	Only changed for debugging purposes
DRServerName	Name of service to receive delivery receipts	DeliveryReciptServer	Only changed for debugging purposes
LogFileName	Name of file to receive log messages	text string	Absolute or relative path to a logger file Directory must exist already.
Database Parameters			
DbClass	The driver to use for talking with the database	text string	Class name to use for database access. System must be configured with proper drivers
DbUrl	The reference to the database and machine where database resides	text string	Legal URL for the driver
DbAccount	Account name	text string	
DbPassword	Password to account	text string	
Delivery Setup Parameters			
MsgGroupSize	Number of messages to send to a subscriber at a time	number	
MsgSendRate	Number of messages to send per minute	number	
MsgHoldTimes	Time to not send msgs (local time). Repeat the line for multiple periods	Start time and end time in 24 hour format, HHMM	Must have start and end times. If end is less than start, then cross over of midnight is assumed.
Polling/Expiration Rates Parameters			
SubscriberOnlineTime	Maximum number of seconds a subscriber stays online	number	
SubscriberOfflineTime	Maximum number of seconds a subscriber stays	number	

Parameter	Purpose	Field Value	Field Explanation
	offline		
SubscriberXmitPoll Time	Time between checks for subscriber messages (seconds)	number	This must be less than half the value of the smaller of SubscriberOnlineTi me & SubscriberOfflineTi me
SubscriberExpireTi me	Hours without a message before a subscriber is purged.	number	

Table 7

IdaRemoteHostInfo.properties File

5   This file relates a link ID for a MIN to a remote host name, and whether it can support delivery receipts. A leading number followed by an underscore corresponds to the link ID in the LINKID_NPANXX table and the GWDest.properties file.

The   form   of   an   entry   in   the   disclosed

10   IdaRemoteHostInfo.properties file may be, e.g., <linkid>_<parameter>=value. Permissible   parameters   and   their   values   for   the   exemplary IdaRemoteHostInfo.properties files are shown in Table 8.

Parameter	Purpose	Values
carrierName	Short form of the carrier name	Text string
carrierNameLong	Long form of the carrier name	Text string
carrierHostname	The host name of the machine with the carrier's remote gateway	The name must be resolvable via DNS.
receiptSupported	Indicates if remote gateway can send delivery receipts. The gateway must be running the updated version of TCS gateway software and have enable_web in smscgw.cfg set to true	true, yes, false or no

Table 8

Table 9 is an example showing how the carrier data may be formatted in the IdaRemoteHostInfo.properties file.

```
0_carrierName=AT
0_carrierNameLong=AirTouch
0_carrierHostname=Sms2way.airtouch.net
0_receiptSupported=yes

3_carrierName=BAM
3_carrierNameLong=Bell Atlantic Mobile
3_carrierHostname=smsc.bam.com
3_receiptSupported=yes

24_carrierName=FR
24_carrierNameLong=Frontier
24_carrierHostname=msg.frontiercellular.com
24_receiptSupported=no
```

Table 9

MDC Configuration File

An smscgw.cfg file may be used to configure the software of the MDC Gateway **100**. The disclosed MDC Gateway **100** requires several

parameters to be set to route short messages from information providers to the IDA **318**. The Remote Gateways that the IDA **318** talks to preferably have a flag such as "enable_web" set if they are to be capable of sending delivery receipts back to the IDA **318**. Tables 10 and 11 show exemplary parameters in an MDC Configuration File, in accordance with the principles of the present invention.

smscgw.cfg MDC Gateway Configuration		
Parameter	**MDC Value**	**Notes**
enable_mdc	yes	Causes check for information provider messages
enable_smtp	yes	Remote gateway routes mail to the IDA.
enable_web	yes	Allows remote queue calls via RMI
MessageStore Type	DB	IDA can only work with database activated

Table 10

smscgw.cfg Remote Gateway Configuration		
Parameter	**MDC Value**	**Notes**
enable_web	yes	Allows remote queue calls via RMI

Table 11

While the invention has been described with reference to the exemplary embodiments thereof, those skilled in the art will be able to make various modifications to the described embodiments of the invention without departing from the true spirit and scope of the invention.

CLAIMS

What is claimed is:

1. A method of providing cross-carrier messaging, comprising:

intercepting a short message from a sending subscriber of a first wireless carrier intended for transmission over an Internet;

storing said intercepted short message in an individual subscriber queue located in a gateway;

determining a destination of said short message based on a mobile identification number (MIN); and

automatically delivering said short message to said receiving subscriber of a second wireless carrier different from said first wireless carrier without transmission over said Internet;

whereby said short message is transmitted between different wireless carriers without requiring transmission over an Internet.

2. The method of providing cross-carrier messaging according to claim 1, wherein:

said short message is transmitted to said second wireless carrier using RMI protocols.

3. The method of providing cross-carrier messaging according to claim 1, wherein:

said short message is transmitted to said second wireless carrier using SMPP protocols.

4. A method of automatically delivering a short message to a mobile device, comprising:

determining when said mobile device has powered up by inspecting SS7 data from a home location register relating to said mobile device; and

automatically delivering said short message to said mobile device when said mobile device has powered up based on information obtained from said inspection of SS7 data.

5. A method of automatically delivering a short message to a mobile device, comprising:

determining when said mobile device has powered up by inspecting delivery receipt data from a short message servicing center relating to said mobile device; and

automatically delivering said short message to said mobile device when said mobile device has powered up based on information obtained from said inspection of said delivery receipt data.

6. Apparatus for providing cross-carrier messaging, comprising:

means for intercepting a short message from a sending subscriber of a first wireless carrier intended for transmission over an Internet;

means for storing said intercepted short message in an individual subscriber queue located in a gateway;

means for determining a destination of said short message based on a mobile identification number (MIN); and

means for automatically delivering said short message to said receiving subscriber of a second wireless carrier different from said first wireless carrier without transmission over said Internet;

whereby said short message is transmitted between different wireless carriers without requiring transmission over an Internet.

7. The apparatus for providing cross-carrier messaging according to claim 6, wherein:

· said means for automatically delivering said short message transmits said short message to said second wireless carrier using RMI protocols.

8. The apparatus for providing cross-carrier messaging according to claim 6, wherein:

said means for automatically delivering said short message transmits said short message to said second wireless carrier using SMPP protocols.

23

9. Apparatus for automatically delivering a short message to a mobile device, comprising:

means for determining when said mobile device has powered up by inspecting SS7 data from a home location register relating to said mobile device; and

means for automatically delivering said short message to said mobile device when said mobile device has powered up based on information obtained from said inspection of SS7 data.

10. Apparatus for automatically delivering a short message to a mobile device, comprising:

means for determining when said mobile device has powered up by inspecting delivery receipt data from a short message servicing center relating to said mobile device; and

means for automatically delivering said short message to said mobile device when said mobile device has powered up based on information obtained from said inspection of said delivery receipt data.

FIG. 1

FIG. 2

FIG. 3

INTERNATIONAL SEARCH REPORT

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) :H04Q 7/18 7/20 7/22; H04M 1/57 1/65 3/50
US CL : 455/466 426 560 556 557 553 575; 370/349 522 524 352 353 354

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 455/466 426 560 556 557 553 575; 370/349 522 524 352 353 354

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5,943,399 A (BANNISTER et al.) 24 August 1999, abstract, fig. 1-9, col. 4, line 61 - col. 8, line 19.	1-10
Y	US 5,946,629 A (SAWYER et al.) 31 August 1999, abstract, fig. 1, 3, col. 3, line 1 - col. 4, line 26, col. 5, line 42 - col. 6, line 55.	1-10
Y	US 5,978,685 A (LAIHO) 02 November 1999, abstract, fig. 1, 5, 7, 8, col. 3, lines 29-65, col. 4, line 10 - col. 5, line 16.	1-10
Y,P	US 6,205,330 B1 (WINBADH) 20 March 2001, abstract, fig. 1-3, col. 3, line 57 - col. 5, line 33, col. 9, lines 9-24.	1-10

☐ Further documents are listed in the continuation of Box C.   ☐ See patent family annex.

*	Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A"	document defining the general state of the art which is not considered to be of particular relevance	
"E"	earlier document published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L"	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O"	document referring to an oral disclosure, use, exhibition or other means	
"P"	document published prior to the international filing date but later than the priority date claimed	"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
15 JUNE 2001	**0 6 AUG 2001**

Name and mailing address of the ISA/US	Authorized officer
Commissioner of Patents and Trademarks Box PCT	PABLO TRAN